

Design Memorandum

TO: All Design Section Staff
FROM: Bijan Khaleghi
DATE: September 3, 2014
SUBJECT: Buried Structures

This design memorandum defines WSDOT policy for use of buried structures. This design memorandum supersedes the design memorandum dated June 30, 2014.

Buried structure systems considered herein are: metal pipe, structural plate pipe, long-span structural plate, deep corrugated plate, reinforced concrete pipe, cast-in-place reinforced concrete and precast concrete arch, box and elliptical structures, thermoplastic pipe, and fiberglass pipe. All buried structures shall comply with the current edition of the AASHTO LRFD Specifications for minimum service life of 75 years. This memorandum applies to all buried structures regardless of contracting methods.

General Requirements:

Buried structure systems considered herein are: metal pipe, structural plate pipe, long-span structural plate, deep corrugated plate, reinforced concrete pipe, cast-in-place reinforced concrete and precast concrete arch, box and elliptical structures, thermoplastic pipe, and fiberglass pipe. Due to lack of satisfactory performance, buried box culverts constructed of aluminum or steel structural plate shall not be used for any types of buried structures regardless of span lengths or usage.

The span length for buried structures regardless of type and materials is limited to 26 feet. On a case-by-case basis, spans beyond 26 feet may be used upon approval of the State Hydraulics, Geotechnical, and Bridge Design Engineers, provided sufficient supporting project specific justification and documentation regarding past performance and compliance with the AASHTO LRFD minimum service life of 75 years is provided. Performance monitoring instrumentation may be required for buried metal structures with spans beyond 26 feet. The span length for buried structures is the widest opening measured along centerline roadway.

For Design-Build projects all buried structures are required to be sealed and signed by licensed Hydraulics, Geotechnical and Structural Engineers.

Design Requirements:

The design of buried structures shall be in accordance with the requirement of current edition of AASHTO LRFD Bridge Design Specifications Section 12, unless otherwise required in the project-specific criteria. The decrease in live load effect due to increase in fill depth shall be considered in both design and load rating of buried structures. The requirement of BDM Section 3.5 for inclusion of live load in Extreme Event-I load combination is applicable. Foundations for buried structures shall be designed and detailed in accordance with Bridge Design, and Geotechnical Manuals.

Seismic Design Requirements:

Seismic design of buried structures shall confirm to Chapter 13 Seismic Considerations in FHWA publication FHWA-NHI-10-034, Technical Manual for Design and Construction of Road Tunnels – Civil Elements. The seismic effects of transient racking/ovaling deformations on culverts and pipe structures must be considered in addition to the normal load effects from dead loads of structural components, vertical and horizontal earth and water loads, and live load surcharges. The AASHTO LRFD Bridge Design Specifications Section 12.6.1 exemption from seismic loading shall not apply.

The seismic design need not be considered for buried structures with span lengths of 20 feet or less. Structures with span lengths as defined above greater than 20 feet shall be designed for seismic effects. The ground motion attenuation as specified below shall be used for seismic design of buried structures.

Table 1: Ground Motion Attenuation with Depth

Depth to Top of Buried Structure, feet	Ratio of Ground Motion at Buried Structure Depth to Motion at Ground Surface
< 20	1.0
20 to 50	0.9
50 to 100	0.8
>100	0.7

For buried structures, with span lengths more than 20 feet, the seismic effects of potential unstable ground conditions (e.g., liquefaction, liquefaction induced settlement, landslides, and fault displacements) on the function of the buried structures shall be considered, except liquefaction need not be considered if the liquefaction, landslides, or fault displacements do not cause life safety hazards. As a guideline, if the depth of fill on top of the structure is more than one-half the clear span along the skew, liquefaction induced settlement or local instability are not likely to cause life safety hazards.

The above provisions are the minimum seismic design requirements for conventional buried structures. Additional provisions may be specified, on a case-by-case basis, to achieve higher seismic performance criteria for essential or critical buried structures. Where such additional

requirements are specified, they shall be site or project specific and are tailored to a particular structure type.

Submittal Requirements:

The design calculations and detailed shop drawings of buried structures shall be submitted to the Bridge and Structures Office for review and approval. The submittal shall include load rating for all buried structures with span length beyond 20 feet. The submittal shall include installation procedures, backfill materials, and compacting sequences. The adequacy of the buried structure for the required depth of fill shall be provided in the submittal. Final as-built plans shall be submitted to the Bridge and Structures Office for records.

The above provisions apply to buried structures composed of precast or Cast-in-place concrete walls supporting the roadway embankment. Precast walls that are being supplied as part of the culvert systems could be preapproved if they meet the WSDOT design and detailing requirement, and the preapproval procedures.

Background:

The main purpose of this design memorandum is to require evaluation of all new non-bridge structures spanning beyond 26 feet. This would require evaluation (by the WSDOT team: Bridge and Structures, Geotechnical, Hydraulics, etc.) of non-bridge structures such as culverts, boxes or similar, when spanning greater than 26 feet.

All buried structures shall comply with the AASHTO LRFD service life of 75 years minimum. Due to lack of satisfactory performance, buried box culverts constructed of aluminum or steel structural plate shall not be used for any types of buried structures regardless of span lengths or usage. Many factors are considered in preliminary design of buried structures. Some of the more common of these are: Stream flow conditions, passage of flood debris, scour, effect of shape, width, skew, bank and pier protection, consideration of a culvert as an alternate solution, and permit requirements for navigation and stream work limitations.

General NBI requirements are that the Bridge Preservation Office has a load rating on file for every structure with span length greater than 20 feet.

Precast walls that are being supplied as part of the culvert systems could be preapproved similar to other preapproved if they meet the WSDOT design and detailing procedures.

If you have any questions regarding this issue, please contact Casey.Kramer@wsdot.wa.gov, Tony.Allen@wsdot.wa.gov, Harvey.Coffman@wsdot.wa.gov, Mark.Szewcik@wsdot.wa.gov, or Bijan Khaleghi at 705-7181 (Bijan.Khaleghi@wsdot.wa.gov).

cc: Mark Gaines, Bridge Construction – 47354
Craig Boone, Bridge and Structures – 47340

BDM Revisions:

BDM section 8.2.1 shall be modified as follows:

Chapter 8 Walls and Buried Structures **Contents**

8.1 Retaining Walls 8.1-1

8.1.1 General . 8.1-1

8.1.2 Common Types of Walls 8.1-1

8.1.3 Design 8.1-3

8.1.4 Miscellaneous Items 8.1-8

8.2 Miscellaneous ~~underground~~ Buried Structures.

8.2.1 General

- A. General Requirements
- B. Design Requirements Seismic
- C. Design Requirements
- D. Submittal Requirements

8.2.2 Design

8.2.3 References

8.2 Miscellaneous ~~Underground~~ Buried Structures

8.2.1 General

Miscellaneous buried structures consist of metal pipe, structural plate pipe, long-span structural plate, deep corrugated plate, reinforced concrete pipe, cast-in-place reinforced concrete and precast concrete arch, box and elliptical structures, thermoplastic pipe, and

fiberglass pipe. All buried structures shall comply with the current edition of the AASHTO LRFD Specifications for minimum service life of 75 years.

The 26 feet span limit is based on the WSDOT past practice for shipping, handling and installation of buried concrete structures.

General NBI requirements are that the Bridge Preservation Office has a load rating on file for every structure with span length greater than 20 feet.

A. General Requirements

Buried structure systems considered herein are: metal pipe, structural plate pipe, long-span structural plate, deep corrugated plate, reinforced concrete pipe, cast-in-place reinforced concrete and precast concrete arch, box and elliptical structures, thermoplastic pipe, and fiberglass pipe. Due to lack of satisfactory performance, buried box culverts constructed of aluminum or steel structural plate shall not be used for any types of buried structures regardless of span lengths or usage.

The span length for buried structures regardless of type and materials is limited to 26 feet. On a case-by-case basis, spans beyond 26 feet may be used upon approval of the State Hydraulics, Geotechnical, and Bridge Design Engineers, provided sufficient supporting project specific justification and documentation regarding past performance and compliance with the AASHTO LRFD minimum service life of 75 years is provided. Performance monitoring instrumentations may be required for buried metal structures with spans beyond 26 feet. The span length for buried structures is the widest opening measured along centerline roadway.

For Design-Build projects all buried structures are required to be sealed and signed by licensed Hydraulics, Geotechnical and Structural Engineers.

B. Design Requirements

The design of buried structures shall be in accordance with the requirement of current edition of AASHTO LRFD Bridge Design Specifications Section 12, unless otherwise required in the project-specific criteria. The decrease in live load effect due to increase in fill depth shall be considered in both design and load rating of buried structures. The requirement of BDM Section 3.5 for inclusion of live load in Extreme Event-I load combination is applicable. Foundations for buried structures shall be designed and detailed in accordance with Bridge Design, and Geotechnical Manuals.

C. Seismic Design Requirements

Seismic design of buried structures shall confirm to Chapter 13 Seismic Considerations in FHWA publication FHWA-NHI-10-034, Technical Manual for Design and Construction

of Road Tunnels – Civil Elements. The seismic effects of transient racking/ovaling deformations on culverts and pipe structures must be considered in addition to the normal load effects from dead loads of structural components, vertical and horizontal earth and water loads, and live load surcharges. The AASHTO LRFD Bridge Design Specifications Section 12.6.1 exemption from seismic loading shall not apply.

The seismic design need not be considered for buried structures with span lengths of 20 feet or less. Structures with span lengths as defined above greater than 20 feet shall be designed for seismic effects. ”The ground motion attenuation as specified below shall be considered used for seismic design of buried structures. Table 1: Ground Motion

Attenuation with Depth

Depth to Top of Buried Structure, feet	Ratio of Ground Motion at Buried Structure Depth to Motion at Ground Surface
< 20	1.0
20 to 50	0.9
50 to 100	0.8
>100	0.7

For buried structures, with span lengths more than 20 feet, the seismic effects of potential unstable ground conditions (e.g., liquefaction, liquefaction induced settlement, landslides, and fault displacements) on the function of the buried structures shall be considered, except liquefaction need not be considered if the liquefaction, landslides, or fault displacements do not cause life safety hazards. As a guideline, if the depth of fill on top of the structure is more than one-half the clear span along the skew, liquefaction induced settlement or local instability are not likely to cause life safety hazards.

The above provisions are the minimum seismic design requirements for conventional buried structures. Additional provisions may be specified, on a case-by-case basis, to achieve higher seismic performance criteria for essential or critical buried structures. Where such additional requirements are specified, they shall be site or project specific and are tailored to a particular structure type.

D. Submittal Requirements

The design calculations and detailed shop drawings of buried structures shall be submitted to the Bridge and Structures Office for review and approval. The submittal shall include load rating for all buried structures with span length beyond 20 feet. The submittal shall include installation procedures, backfill materials, and compacting sequences. The adequacy of the buried structure for the required depth of fill shall be provided in the submittal. Final as-built plans shall be submitted to the Bridge and Structures Office for records.

The above provisions apply to buried structures composed of precast or Cast-in-place concrete walls supporting the roadway embankment. Precast walls that are being supplied as part of the culvert systems could be preapproved if they meet the WSDOT design and detailing requirement, and the preapproval procedures.